

You need fresh air, so does your home.



## Greentek Peace of Mind

All Greentek products are backed by the best limited warranty in the industry, for your peace of mind.

You benefit from a lifetime warranty on the core, a 10-year warranty on our ventilation motors and a 5-year warranty on all other components. So you can breathe easy.





Imperial

## Heat Recovery Ventilator PH Series (PH 7.15 and PH 10.22)



## **Green**tek

## Features & Benefits



DuoTrol balancing system

Silent and economical... By reducing motor speed to balance the unit, you avoid the noise that would

be produced by balancing dampers. In addition, with this technology the unit will consume less energy.



SPM attachment system

The entire line of Greentek HRV/ERV products is designed for installation by a single person. "Single Person

Mounting" will enable you to save time and effort by offering you a variable attachment system.



**ISF** 6" (diam.) collar system (Patent Pending)

Quick and simple to install thanks to our revolutionary "Insert Slide and Fix"

collar system. The "ISF" 6" (diam.) collar system enables you to manipulate duct within your reach and then insert by sliding it in place, for a better and quicker installation.



Range of controls For optimal performance of your HRV/ERV system.

The entire range of GreenThinker controls is offered with features making

your ventilation system simple, easy to operate and backed by a 5-year limited warranty.

Choose from: RD-1, RD-2, RD-3P, RD-4P (shown above) and T-3 (Push-Button Timer)




**Engineered motors** 

All Greentek products are designed with highperformance and reliable motors for your comfort and

peace of mind. Factory sealed and dynamically balanced, our motors are maintenance-free for years to come.

Ven	tilation	Perfo	orman	ce PH	7.15			
External Static Pressure		Net Supply Air Flow			Air Flow oply	Gross Air Flow Exhaust		
Pa	in. wg	L/s	CFM	L/s	CFM	L/s	CFM	
25	0.1	92	195	92	196	113	241	
50	0.2	85	182	86	183	105	223	
75	0.3	80	171	81	172	91	193	
100	0.4	73	156	74	157	84	178	
125	0.5	65	139	66	140	75	159	
150	0.6	59	126	60	127	65	137	
175	0.7	56	120	57	120	57	120	
HVI	Tested by: Boo	lycote Mate	rial Testing (	Canada Inc. ((	Ortech)			



	al Static ssure		Supply Flow		Air Flow oply		Air Flow aust			_	- <b>→</b> Su	pply <b>=</b> E:	xhaust
Pa	in. wg	L/s	CFM	L/s	CFM	L/s	CFM		0.8				
25	0.1	117	248	118	250	130	277	External Static Pressure in wg (Pa = n x 248.36)	0.7				
50	0.2	108	229	109	231	119	253	Pres	0.5				
75	0.3	102	218	103	220	110	234	atic "n x	0.4			+N	
100	0.4	94	200	95	202	101	216	St.	0.3			$\bot$	
125	0.5	85	181	86	183	92	197	External S in wg (Pa	0.2				$\mathcal{L}$
150	0.6	77	163	78	165	82	175	i K	0.1				AY
175	0.7	69	146	70	148	71	151		۰	50	100	150 200	250 30
	Tested by: Bod	lycote Mate	rial Testing (	Canada Inc. (0	Ortech)				U			= n x 0.4719	

Er	ner	gy F	erf	orm	nance	PH 7	'.15
1	Sup Tempe	ply rature		let Flow	Power Consumed	Sensible Recovery	Apparent Sensible
	°C	°F	L/s	CFM	Watts	Efficiency	Effectiveness
5	0	32	31	66	88	66	78
HEATING	0	32	42	89	104	64	76
3	0	32	56	119	114	63	72
ä	-25	-13	32	67	86	59	77

E	ner	gy F	erf	orm	nance	PH 1	0.22
	Sup Tempe	ply rature		let Flow	Power Consumed	Sensible Recovery	Apparent Sensible
	°C	°F	L/s	CFM	Watts	Efficiency	Effectiveness
16	0	32	55	118	106	61	71
É	0	32	75	160	132	58	65
V	0	32	87	185	150	55	62
Ë	-25	-13	57	120	105	58	72
HEATING	•						

SPECIFICATIONS	PH 7.15	PH 10.22
Size	23%" x 21½" x 11%"	23½" x 21½" x 16½"
Weight	50 lbs (22.68 Kg)	65 lbs (29.48 Kg)
CFM	30 to 160	50 to 220
Type of heat exchanger	cross-flow (Polypropylene)	cross-flow (Polypropylene)
Exchange surface	104 ft <sup>2</sup>	150 ft <sup>2</sup>
Voltage	120 VAC @ 60 Hz	120 VAC @ 60 Hz
Amperage	1.5 A	1.5 A
Defrost type	Evacuation	Evacuation
Certification	HVI, QPS, SGSUSTC	HVI, CCSAUS
	211/2" 6"	211/2"
Also available in PE Series (Energy Recove	ery Ventilator). Ideal for warm and humid climates.	, i



Imperial Air Technologies Inc. 480 Ferdinand Blvd., Dieppe, NB Canada E1A 6V9

Toll free: 1 888 724-5211 Fax: 1 (506) 388-4633 Visit us at: www.greentek.ca

You can find Greentek Indoor Air Quality products at the following distributor:













